

# Discrete Output Module (DOM)

Fully Qualified Safety-Related Digital Platform

**CURTISS-  
WRIGHT**



## About

Curtiss-Wright Nuclear has partnered with Radics, LLC to supply integrated FPGA-based instrumentation and control (I&C) systems for nuclear power plants and research reactors. RadICS is a digital I&C platform that is robust, flexible, and scalable. It provides state-of-the-art functions, services, and safeguards for safety applications in the nuclear industry. The RadICS product line consists of a Logic Module, basic input/output modules, and specialty modules all housed in a seismically qualified chassis.

The Discrete Output Module (DOM) is a high-density device providing 32 independent, highly reliable, and optically isolated discrete outputs. The Logic Module uses the DOM to drive field devices, indicators, and other functions. The DOM also performs robust and continuous self-diagnostics to ensure the safety and integrity of each output and module function. In the event of critical failures, the DOM deenergizes to a safe-state.

## Discrete Output Module (DOM)

- High density 32 channel Form-A optically isolated, fuse and overvoltage protected discrete outputs.
- Independent FPGA for discrete output processing, self-diagnostics, and fail-safe functional behavior.
- IEC 61508 SIL 3 certification in single and multiple channel configurations.
- Robust self-diagnostics ensure higher reliability and early fault detection with safety-focused fault management.
- Segregation of output processing, self-diagnostics, and watchdog functions assures safety-critical functionality.
- Galvanic isolation for signal outputs with robust and dedicated communication links to Logic Module for secure data transfer.
- Inherent on-board diversity features eliminate common cause failure vulnerabilities.
- FPGA technology ensures cyber security resilience to obsolescence.



# Discrete Output Module (DOM)

Fully Qualified Safety-Related Digital Platform

## Discrete Output Module Technical Specifications

Function	Specifications
Output Channel Load Voltage / Current (maximum switching voltage / current)	up to 48 VDC, 0.2 amp, Form A contact
Output Channel Isolation	all output channels are galvanic-isolated up to 250 V <sub>RMS</sub> AC or 250 VDC field-to-Chassis and channel-to-channel
Output Channel Isolation Method	optical relay
Output Overvoltage Protection	up to $\pm 60$ VDC/VAC continuous (using external protection elements installed in Chassis)
Information Package Exchange Cycle	5 milliseconds
Diagnostic Package Exchange Cycle	5 milliseconds
LVDS Line Speed	100 megabit/second
LVDS Line Protocol	proprietary protocol with integrity checking (CRC), galvanic-isolated Tx / Rx
Fiber Optical Lines Speed	100 megabit/second
Self-Diagnostic Functions	diverse watchdog unit, checksum analysis, active diagnostics with internal fault detection, hardware error detection, functionally diverse continuous self-diagnostic tests, power supply fault detection
Power Supply / Consumption	2 independent inputs – 24 (18 – 36) VDC / Maximum consumption: 0.63A ( $\pm 0.15$ A) (32 outputs used; all outputs closed)
Indications	2 status LED indicators (RUN/FAULT) 4-character dot matrix symbol-indicator for providing current operational mode, service information, and error codes
Operating Temperature	4.4 to 60 °C (40 to 140 °F)
Operating Humidity	10 to 90% relative humidity, non-condensing

### CONTACT INFORMATION:

1350 Whitewater Dr., Idaho Falls, ID 83402 USA  
Tel: +1.208.497.3535 | DSS-Sales@curtisswright.com