

# Graphite Mechanical Packing

AP STYLE 620/620C

**CURTISS -  
WRIGHT**



## AP Style 620/620C

Style 620 is a flexible, all metallic packing constructed from aluminum foil, which has been treated, heavily lubricated, and crinkle wrapped to a square cross section. Style 620C is of the same durable construction as 620 with the addition of a resilient fiberglass core.

Aluminum foil is recommended for oil, dowtherm, acids, air and water, on hot oil pumps. When used on pumps, the sleeves should be minimum 400 Brinell hardness. Style 620 and 620C are available as individual rings and in bulk.

## Typical Properties

<b>Maximum Temperature</b>
1,000 °F
<b>Maximum Shaft Speed</b>
2,000 FPM
<b>Ph Range</b>
4-10
<b>Construction</b>
Crinkled

## Standard Sizes

in.	1/8	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8	3/4	7/8	1
ft./lb.	66	37	23	13.7	10	7.5	6.2	5.8	3.8	3.1	2.7	2.3

## CONTACT INFORMATION:

18001 Sheldon Road, Middleburg Hts., OH 44130  
+1.216.267.3200 | [cwnuclear.com](http://cwnuclear.com)